

# Floor protection plate ASGLAPLATE light

made in Germany



The new ASGLAPLATE light ground protection plate is an innovative solution for protecting the floor at events. It is characterised above all by its lightness and high stability thanks to the glass fibre reinforcement. Thanks to the combination of the material with the click system, the ASGLAPLATE light can be installed quickly and easily by one or two employees. This saves resources and installation time.

The size of the plate corresponds to the practical standard size of a Euro pallet. Making transport considerably easier, as no special haulage company is required. Furthermore, the panels are weather-resistant and can withstand various environmental conditions without losing quality. The floor protection plates are made of a break-resistant and durable material, meaning that a compacted substructure is generally not necessary. This saves further costs and labour. Another key advantage is sustainability, as the plates are fully recyclable.

On customer request, the floor protection plates can be produced with a customised logo or special lettering, which makes the plates usable for branding and marketing purposes.

Application	Plate that can be walked on and driven on with light equipment, e.g. for events
Material	Polypropylene with glass fibre content
Load Capacity	Surface load up to 250 tonnes on paved ground * Wheel load up to 25 tonnes *
Area	Effective cover area 0,825 m <sup>2</sup>
Size	1.171 mm x 801 mm x 5 mm
Weight per plate	5.5 kg
Colour	Black
Joining technique	Click system without connecting elements
Surface	Nonskid surface
Chemical resistance	Resistant to chemicals **

\* The specified load capacities are to be understood as guide values. An assessment of the ground by the user and advice from ASGLAFORM composites GmbH is recommended before use. When used, the floor protection plates must have full-surface contact with the load-bearing ground for load distribution. Surface load determined with full-surface, uniform load. Wheel load determined under load from standard truck twin tires with tire dimensions of 295/80 R22.5.

\*\* List available on request